measurement SPECIALTIES

Model 3031 Accelerometer

SMD Accelerometer
Miniature DC Response
Piezoresistive MEMS
10,000g Over-Range Protection

The Model 3031 is a silicon MEMS accelerometer designed for demanding mid to high volume applications. The accelerometer is ideal for applications requiring a miniature light weight accelerometer with wide frequency bandwidth. The model 3031 incorporates a 3rd generation MEMS sensing element providing superior long-term stability. The accelerometer provides a millivolt output signal and features mechanical overload stops that provide shock protection to 10,000g.

dimensions



FEATURES

- ±50g to ±100g Range (higher ranges available on model 3038)
- Surface Mount Package
- 3rd Generation MEMS Element
- Light Weight
- DC Response, Gas Damping
- Over-Range Stops
- Low Power Consumption

APPLICATIONS

- Vibration & Shock Monitoring
- Embedded Applications
- Surface Mount Package
- Machinery
- Transportation
- Instrumentation



US Patents 5,103,667; 5,253,510; 5,445,006 apply

32 Journey Ste. 150 Aliso Viejo, CA 92656 949-716-5377 enduser@meas-spec.com

Supporting your great ideas www.pewatron.com PEWATRON a member of the Angst + Pfister Group

Model 3031 Accelerometer

performance specifications

All values are typical at +24°C, 100Hz and 5Vdc excitation unless otherwise stated. Measurement Specialties reserves the right to update and change these specifications without notice.

Parameters			Notes
DYNAMIC			
Range (g)	±50	±100	
Sensitivity (mV/g)	0.6-1.5	0.3-0.6	@5Vdc Excitation
Frequency Response (Hz)	0-1000	0-1500	±5%
Natural Frequency (Hz)	4000	6000	
Non-Linearity (%FSO)	±0.5	±0.5	
Transverse Sensitivity (%)	<3	<3	<1 Typical
Damping Ratio	0.7	0.7	
Shock Limit (g)	10000	10000	
ELECTRICAL			
Zero Acceleration Output (mV)	±25	±25	Differential
Excitation Voltage (Vdc)	2 to 10	2 to 10	
Input Resistance (Ω)	2500 to 6500	2500 to 6500	
Output Resistance (Ω)	2500 to 6500	2500 to 6500	
Insulation Resistance (MΩ)	>100	>100	@50Vdc
Residual Noise (µV RMS)	10	10	Maximum
Ground Isolation	Isolated from Mounting Surface		
ENVIRONMENTAL			
Thermal Zero Shift (%FSO/°C)	-0.09	-0.09	Typical
Thermal Sensitivity Shift (%/°C)	-0.15	-0.15	Typical
Operating Temperature (°C)	-40 to 125		
Compensated Temperature (°C)	Not Compensated		
Storage Temperature (°C)	-40 to 125		
PHYSICAL			
Case Material	Ceramic		
Cable	Not applicable		
Weight (grams)	0.3		
Mounting	Solder		
Mounting Torque	Not applicable		
AWG	Not applicable		

Wiring color code: Not applicable

The information in this sheet has been carefully reviewed and is believed to be accurate; however, no responsibility is assumed for inaccuracies. Furthermore, this information does not convey to the purchaser of such devices any license under the patent rights to the manufacturer. Measurement Specialties, Inc. reserves the right to make changes without further notice to any product herein. Measurement Specialties, Inc. makes no warranty, representation or guarantee regarding the suitability of its product for any particular purpose, nor does Measurement Specialties, Inc. assume any liability arising out of the application or use of any product or circuit and specifically disclaims any and all liability, including without limitation consequential or incidental damages. Typical parameters can and do vary in different applications. All operating parameters must be validated for each customer application by customer's technical experts. Measurement Specialties, Inc. does not convey any license under its patent rights nor the rights of others.

ordering info

PART NUMBERING Model Number+Range

3031-GGG
|
|_____Range (050 is 50 g)

Example: 3031-050
Model 3031, 50g

32 Journey Ste. 150 Aliso Viejo, CA 92656 949-716-5377 enduser@meas-spec.com

Supporting your great ideas www.pewatron.com PEWATRON a member of the Angst + Pfister Group

PEWATRON
a member of the Angst + Pfister Group

We are here for you. Addresses and Contacts

Sales Switzerland

Postcode 3000 – 9999
Liechtenstein

Matthias Rüegg
Ruhbergstrasse 32
CH-9230 Flawil

Phone + 41 44 877 35 18
Mobile + 41 76 491 66 66
Fax + 41 44 877 35 19

matthias.rueegg@pewatron.com

Postcode 1000 – 2999

Raffael Favaretto
Route d'Oron 124
CH-1673 Promasens

Phone + 41 44 877 35 22
Mobile + 41 76 444 63 14
Fax + 41 44 877 35 23

raffael.favaretto@pewatron.com

Sales Germany

Postcode 60000 – 79999

Dieter Hirthe
Mühlweg 23
D-71554 Weissach i.T.

Phone + 49 719 149 60 58
Mobile + 49 163 762 74 30
Fax + 49 719 193 31 88

dieter.hirthe@pewatron.com

Postcode 10000 – 59999
Postcode 80000 – 99999

Kurt Stritzelberger
Neumarkter Str. 86a
D-81673 Munich

Phone + 49 89 260 38 47
Mobile + 49 171 803 41 35
Fax + 49 89 43 10 91 91

kurt.stritzelberger@pewatron.com

Key Accounts
Aerospace and Defence

Claus Wübbena
Vogelkamp 26
D-26655 Westerstede

Phone + 49 4488 5204 614
Mobile + 49 173 9700 691
Fax + 49 4488 5204 616

claus.wuebbena@pewatron.com

Sales Austria

Kurt Stritzelberger
Neumarkter Str. 86a
D-81673 Munich

Phone + 49 89 260 38 47
Mobile + 49 17 18 03 41 35
Fax + 49 89 43 10 91 91

kurt.stritzelberger@pewatron.com

Sales Other Countries / Product Management

Sensors

Physical Sensors
Data Acquisition

Peter Felder
Phone + 41 44 877 35 05
peter.felder@pewatron.com

Geometrical Sensors

Eric Letsch
Phone + 41 44 877 35 14
eric.letsch@pewatron.com

Power Supplies

DC-DC Converters
Switching Power Supplies
DC-AC Inverters

Sebastiano Leggio
Phone + 41 44 877 35 06
sebastiano.leggio@pewatron.com

E-Components

Current Sensors
Man Machine Interface
Measurement Probes

Sebastiano Leggio
Phone + 41 44 877 35 06
sebastiano.leggio@pewatron.com

PEWATRON AG
Thurgauerstrasse 66
CH-8052 Zurich

Phone + 41 44 877 35 00
Fax + 41 44 877 35 25

www.pewatron.com
info@pewatron.com