























# ABSOLUTE ENCODER

## SINGLETURN ABSOLUTE ASSOLUTI MONOGIRO




Model Modello		Dimensions (mm) Dimensioni (mm)	Shaft diameter (mm) Diametro albero (mm)	Max resolution Risoluzione max	Max enclosure rating Grado di protezione max	Max rotation speed Velocità max	Outputs Uscite	Code Tipo di codice	Power supply Tensione di alimentazione	Operating temperature Temperatura di funzionamento
<b>EA 40</b> A/B		∅ 42 □ 44	∅ 6	8 bit	IP 66	6.000 rpm	Npn / Npn open collector / Pnp / Pnp open collector	Gray	5 Vdc 8 ... 28 Vdc	-10°... +60°C
<b>EA 58</b> B/C/F		∅ 58 ∅ 64	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10 / ∅ 12 / ∅ 14 / ∅ 15	13 bit	IP 66	6.000 rpm	Npn / Npn open collector / Pnp / Pnp open collector / Push pull / Line driver SSI / Profibus /	Binary Gray Ico	5 Vdc 8 ... 28 Vdc 12 ... 28 Vdc	0°... +60°C
<b>EA 63</b> A/D/E/F/G		∅ 64 □ 63,5	∅ 8 / ∅ 9,52 / ∅ 10 / ∅ 12 / ∅ 14 / ∅ 15	13 bit	IP 66	6.000 rpm	Npn / Npn open collector / Pnp / Pnp open collector / Push pull / Line driver SSI / Profibus /	Binary Gray Ico	5 Vdc 8 ... 28 Vdc 12 ... 28 Vdc	0°... +60°C
<b>EA 90</b> A		∅ 90	∅ 8 / ∅ 9,52 / ∅ 10	13 bit	IP 66	6.000 rpm	Npn / Npn open collector / Pnp / Pnp open collector / Push pull / Line driver SSI / Profibus /	Binary Gray	5 Vdc 8 ... 28 Vdc 12 ... 28 Vdc	0°... +60°C
<b>EA 115</b> A		∅ 115	∅ 10 / ∅ 11	13 bit	IP 54	6.000 rpm	Npn / Npn open collector / Pnp / Pnp open collector / Push pull / SSI / Profibus	Binary Gray	5 Vdc 8 ... 28 Vdc 12 ... 28 Vdc	0°... +60°C
<b>EA 63</b> AX* / DX*		∅ 63,5 □ 63,5	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10	13 bit	IP 66	3.000 rpm	SSI / Profibus	Binary Gray	5 Vdc 8 ... 28 Vdc 12 ... 28 Vdc	0°... +60°C
<b>EA 120</b> P		∅ 120	∅ 30 / ∅ 40 / ∅ 50 / ∅ 50,8	13 bit	IP 54	3.000 rpm	Push pull / SSI / Line driver	Binary Gray Ico	5 Vdc 8 ... 28 Vdc	0°... +60°C

## MULTITURN ABSOLUTE ASSOLUTI MULTIGIRO

<b>EAM 58</b> B/C/F		∅ 58 ∅ 60	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10 / ∅ 12 / ∅ 14 / ∅ 15	25 bit	IP 66	6.000 rpm	Push pull / SSI / Profibus	Binary Gray	5 Vdc 8 ... 28 Vdc 12 ... 28 Vdc	0°... +60°C
<b>EAM 63</b> A/D/E/F/G		∅ 64 □ 63,5	∅ 8 / ∅ 9,52 / ∅ 10 / ∅ 12 / ∅ 14 / ∅ 15	25 bit	IP 66	6.000 rpm	Push pull / SSI / Profibus	Binary Gray	5 Vdc 8 ... 28 Vdc 12 ... 28 Vdc	0°... +60°C
<b>EAM 90</b> A		∅ 90	∅ 8 / ∅ 9,52 / ∅ 10	25 bit	IP 66	6.000 rpm	Push pull / SSI / Profibus	Binary Gray	5 Vdc 8 ... 28 Vdc 12 ... 28 Vdc	0°... +60°C
<b>EAM 115</b> A		∅ 115	∅ 10 / ∅ 11	25 bit	IP 54	6.000 rpm	Push pull / SSI / Profibus	Binary Gray	5 Vdc 8 ... 28 Vdc 12 ... 28 Vdc	0°... +60°C
<b>EAM 63</b> AX* / DX*		∅ 63,5 □ 63,5	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10	25 bit	IP 66	3.000 rpm	Profibus	-	12 ... 28 Vdc	0°... +60°C

Model Modello		Dimensions (mm) Dimensioni (mm)	Shaft diameter (mm) Diametro albero (mm)	Max resolution Risoluzione max	Max enclosure rating Grado di protezione max	Max rotation speed Velocità max	Outputs Uscite	Code Tipo di codice	Power supply Tensione di alimentazione	Operating temperature Temperatura di funzionamento
EMA - EMS 22 A / AY*		∅ 22	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10	13 bit	IP 68	10.000 rpm	SSI / Sin-Cos	Binary	5 Vdc	-40°... +125°C
EMA - EMS 38 F / G		∅ 39,5	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10	13 bit	IP 67	6.000 rpm	SSI / Sin-Cos	Binary	5 Vdc 8 ... 28 Vdc	-25°... +100°C
EMA - EMS 40 A		∅ 42	∅ 4 / ∅ 6	13 bit	IP 65	6.000 rpm	SSI / Sin-Cos	Binary	5 Vdc 8 ... 28 Vdc	-25°... +100°C
EMA 50 A / AY* / B / BY*		∅ 50	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10	13 bit	IP 67	5.000 rpm	Npn / Npn open collector / Pnp / Pnp open collector / Push pull / SSI	Binary Gray	5 Vdc 8 ... 30 Vdc	-25°... +85°C
EMA 50 F / FY* / G / GY*		∅ 50	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10 / ∅ 12 / ∅ 14 / ∅ 15	13 bit	IP 67	5.000 rpm	Npn / Npn open collector / Pnp / Pnp open collector / Push pull / SSI	Binary Gray	5 Vdc 8 ... 30 Vdc	-25°... +85°C
EMA - EMS 55 A / AY*		∅ 55	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10	13 bit	IP 67	10.000 rpm	SSI / Sin-Cos	Binary	5 Vdc 8 ... 28 Vdc	-25°... +100°C
EMA - EMS 63 A / D / AX* / DX*		∅ 63,5 □ 63,5	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10	13 bit	IP 66	6.000 rpm	Npn / Npn open collector / Pnp / Pnp open collector / Push pull / SSI	Binary Gray	5 Vdc 8 ... 30 Vdc	-25°... +85°C
EML 38 F / G		∅ 39,5	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10	8 bit	IP 67	6.000 rpm	0 ... 5 V / 0 ... 10 V / 0 ... 20 mA / 4 ... 20 mA	-	5 Vdc 12 ... 28 Vdc	-25°... +100°C
EML 50 A / AY* / B / BY*		∅ 50	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10	12 bit	IP 67	5.000 rpm	0 ... 5 V / 0 ... 10 V / 0 ... 20 mA / 4 ... 20 mA	-	5 Vdc 12 ... 28 Vdc	-25°... +85°C
EML 50 F / FY* / G / GY*		∅ 50	∅ 6 / ∅ 8 / ∅ 9,52 / ∅ 10 / ∅ 12 / ∅ 14 / ∅ 15	12 bit	IP 67	5.000 rpm	0 ... 5 V / 0 ... 10 V / 0 ... 20 mA / 4 ... 20 mA	-	5 Vdc 12 ... 28 Vdc	-25°... +85°C

ASSOLUTI MONOGIRO MAGNETICI  
SINGLETURN ABSOLUTE MAGNETIC

EA 40 T / U		∅ 42	∅ 6	4 bit	IP 66	3.000 rpm	Npn / Npn open collector / Pnp / Pnp open collector	Binary	5 Vdc 8 ... 28 Vdc	0°... +60°C
EAX 80 A / D / AX* / DX*		∅ 80 □ 80	∅ 6 / ∅ 8 / ∅ 10	13 bit	IP 65	3.000 rpm	Npn / Npn open collector / Pnp / Pnp open collector / Push pull / SSI	Binary Gray	5 Vdc 8 ... 28 Vdc	0°... +50°C
EAMX 80 A / D / AX* / DX*		∅ 80 □ 80	∅ 6 / ∅ 8 / ∅ 10	13 bit	IP 65	3.000 rpm	SSI	Binary Gray	5 Vdc 8 ... 28 Vdc	0°... +50°C

ASSOLUTI SPECIALI  
SPECIAL ABSOLUTE\*  
X = stainless steel / inox  
Y = anodized / anodizzato

Headquarter Switzerland:  
Pewatron AG  
Thurgauerstrasse 66  
CH-8050 Zurich  
Phone +41 44 877 35 00  
info@pewatron.com

Office Germany:  
Pewatron Deutschland GmbH  
Edisonstraße 16  
D-85716 Unterschleißheim  
Phone +49 89 374 288 87 00  
info.de@pewatron.com



**PEWATRON**  
SENSORS · POWER SOLUTIONS

## We are here for you. Addresses and Contacts.

---

### Sales Germany & Austria

#### Geometrical sensors Other products

Kurt Stritzelberger  
Phone +49 89 374 288 87 22  
kurt.stritzelberger@pewatron.com

#### Pressure sensors Other products

Gerhard Vetter  
Phone +49 89 374 288 87 26  
gerhard.vetter@pewatron.com

#### Gas sensors and modules

Peter Felder  
Phone +41 44 877 35 05  
peter.felder@pewatron.com

---

### Sales Switzerland & Liechtenstein

Postcode 3000 – 9999

Basil Frei  
Phone +41 44 877 35 18  
basil.frei@pewatron.com

Postcode 1000 – 2999

Christian Mohrenstecher  
Phone +41 76 444 57 93  
christian.mohrenstecher@pewatron.com

### Sales International Key Accounts

Peter Felder  
Phone +41 44 877 35 05  
peter.felder@pewatron.com

---

### Sales Other Countries / Product Management

#### Pressure Sensors Load Cells

Philipp Kistler  
Phone +41 44 877 35 03  
philipp.kistler@pewatron.com

#### Gas sensors Gas sensor modules

Dr. Thomas Clausen  
Phone +41 44 877 35 13  
thomas.clausen@pewatron.com

#### Flow / Level / Medical products

Dr. Adriano Pittarelli  
Phone +49 89 374 288 87 67  
adriano.pittarelli@pewatron.com

#### Power supplies

Sebastiano Leggio  
Phone +41 44 877 35 06  
sebastiano.leggio@pewatron.com

#### Linear position sensors Angle sensors

Eric Letsch  
Phone +41 44 877 35 14  
eric.letsch@pewatron.com

#### Accelerometers Sensor elements

Christoph Kleye  
Phone +49 89 374 288 87 61  
christoph.kleye@pewatron.com

#### Drive technology

CH Postcode 5000 – 9999 / DE

Roman Homa  
Phone +41 76 444 00 86  
roman.homa@pewatron.com

#### Drive technology

CH Postcode 1000 – 4999 / AT / IT / FR

Christian Mohrenstecher  
Phone +41 76 444 57 93  
christian.mohrenstecher@pewatron.com

#### Harald Thomas

Phone +49 89 374 288 87 23  
harald.thomas@pewatron.com