

Board Level Pressure Sensors Digital Output

14-Bit, Pressure Sensors

Product	Pressure Range	Op. Temp. [°C]	Accuracy [%FS]	Total Error [%FS]	Size [mm]	Typical Application
Differential/Gage Pressure, barbed pressure ports, 3.3V or 5V, 3mA, 1.5ms conversion time, I²C+SPI interface						
MS4515DO	2, 4, 5, 10, 20, 30 in H ₂ O	-10 to +85	±0.25	±1.0	12.45 x 9.90	Blocked Filter Detection, Medical Instruments
MS4525DO	1, 5, 15, 30, 50, 100, 150psi	-25 to +105	±0.25	±1.0	12.45 x 9.90	Factory Automation, Medical Instruments



16-Bit, Ultra Low Power Pressure Sensors

Product	Pressure Range	Op. Temp. [°C]	Resolution [mbar]	Error [mbar]	Size [mm]	Typical Application
Absolute Pressure, 2.2 to 3.6V, 5uA, 35ms conversion time, SPI compatible interface						
MS5534CP	10 to 1100mbar	-40 to +125	0.1	±1.5	9 x 9	Indoor Barometer/Altimeter
MS5534CM						Outdoor Barometer/Altimeter
MS5535C	14bar	-40 to +125	1.2	±25	9 x 9	Diving Computer 130m
MS5535-30C	30bar					Diving Computer 300m
MS5540CM	10 to 1100mbar	-40 to +85	0.1	±1.5	6.2 x 6.4	Altimeter Watch, Bike Computer
MS5541CM	14bar	-40 to +85	1.2	±25	6.2 x 6.4	Diving Watch 130m
MS5561BM	1bar	-40 to +85	0.1	±1.5	4.25 x 4.75	GPS Altimeter
Differential/Gage Pressure						
MS5536-60	60mbar	-40 to +85	0.05	±1.0	10 x 13	Airspeed Measurement
MS5536-CPJU	-400 to +1000mbar	-40 to +85	0.1	±2.5	10 x 13	CPAP, Sleep Apnea, Airspeed, Blood Pressure
MS5536-CNJU	-1000 to +400mbar					



24-Bit, Ultra Low Power Pressure Sensors

Product	Pressure Range	Op. Temp. [°C]	Resolution [mbar]	Error [mbar]	Size [mm]	Typical Application
Absolute Pressure, <u>no gel</u>, 1.8 to 3.6V, 1uA, 0.5 to 8.2ms conversion time, I²C+SPI interface, internal clock						
MS5607-02BA	10 to 1200mbar	-40 to +85	0.024	±1.5	5 x 3 x 1	GPS Altimeters, Mobile Phones
MS5611-01BA	like MS5607-BP but with double resolution of 0.012mbar, for variometers					
Absolute Pressure, <u>gel-filled</u>, for outdoor products						
MS5803-01BA	10 to 1300mbar		0.012	±1.5		Altimeter Watch, Bike Computer
MS5803-02BA	10 to 2000mbar		0.024	±3.0		Altimeter Watch, Bike Computer
MS5803-05BA	5bar	-40 to +85	0.036	±4.5	6.2 x 6.4	Dual Range Altimeter/Diving
MS5803-14BA	14bar		0.15	±20		Diving Watch 130m
MS5803-30BA	30bar		0.36	±50		Diving Watch 300m
MS5805-02BA	10 to 2000mbar	-40 to +85	0.024	±3.0	4.5 x 4.5	Miniature Altimeter Watch
Absolute/Differential Pressure, high resolution						
MS4515HRD	2, 4, 5, 10, 20, 30 in H ₂ O	-10 to +85	0.001 to 0.005	±0.1 to ±0.5	12.45 x 9.90	Blocked Filter Detection, Medical Instruments
MS4525HRD	1, 5, 15, 30, 50, 100, 150psi	-25 to +105	0.005 to 0.15	±0.25	12.45 x 9.90	High Precision Medical Instruments



Board Level Pressure Sensors Analog Output

Amplified & Compensated Output

Product	Pressure Range	Op. Temp. [°C]	Accuracy [%FS]	Total Error [%FS]	Size [mm]	Typical Application
Differential/Gage Pressure, barbed pressure ports, 3.3V or 5V, 3mA, ratiometric analog output voltage						
MS4515	2, 4, 5, 10, 20, 30 in H ₂ O	-10 to +85	±0.25	±1.0	12.45 x 9.90	Blocked Filter Detection, Medical Instruments
MS4525	1, 5, 15, 30, 50, 100, 150psi	-25 to +105	±0.25	±1.0	12.45 x 9.90	Factory Automation, Medical Instruments



mV Output

Product	Pressure Range	Op. Temp. [°C]	Span [mV/5V]	Linearity [%FS]	Size [mm]	Feature
SMD Uncompensated						
1451	5, 15, 30, 50, 100, 250, 500psi	-40 to +125	60	±0.25	7.6 x 7.6	Tube, Narrow Hole, Wide Hole
MS52XX	1, 12bar	-40 to +125	150 240	± 0.05 ± 0.15	7.6 x 7.6	High Linearity, High Sensitivity Option
MS54XX	1, 7, 12bar	-40 to +125	150 240 392	±0.05 ±0.15 ±0.3	6.2 x 6.4	Gel-filled, Waterproof, for Sealing with O-Ring
SMD compensated						
1471	5, 15, 30, 50, 100, 250, 500psi	-40 to +125	65	±0.25	7.6 x 7.6	Tube, Narrow Hole, Wide Hole
DIL compensated						
1210	5, 10 in H ₂ O	-40 to +125	50mV & 100mV	±0.1	15.2 x 20.3	Temperature Compensated
1220						Ultra Stable (1230/40)
1230						Current Ex. (1210/30)
1240						Voltage Ex. (1220/40)



Headquarter Switzerland:
Pewatron AG
Thurgauerstrasse 66
CH-8050 Zurich
Phone +41 44 877 35 00
info@pewatron.com

Office Germany:
Pewatron Deutschland GmbH
Edisonstraße 16
D-85716 Unterschleißheim
Phone +49 89 374 288 87-0
info.de@pewatron.com



PEWATRON
SENSORS · POWER SOLUTIONS

We are here for you. Addresses and Contacts.

Sales Germany & Austria

Postcode 00000 – 31999
Postcode 38000 – 39999
Postcode 80000 – 99999
Austria

Kurt Stritzelberger

Phone +49 89 260 52 80
Mobile +49 171 803 41 35

kurt.stritzelberger@pewatron.com

Postcode 32000 – 37999
Postcode 40000 – 79999

Gerhard Vetter

Phone +49 674 394 75 75
Mobile +49 163 762 74 30

gerhard.vetter@pewatron.com

Geometrical sensors
Sensor elements

Thorsten Ravagni

Phone +49 60 479 53 627

thorsten.ravagni@pewatron.com

Sales Switzerland & Liechtenstein

Postcode 3000 – 9999

Basil Frei

Phone +41 44 877 35 18
Mobile +41 76 279 37 26

basil.frei@pewatron.com

Postcode 1000 – 2999

Christian Mohrenstecher

Mobile +41 76 444 57 93

christian.mohrenstecher@pewatron.com

Sales International Key Accounts

Peter Felder

Phone +41 44 877 35 05
Mobile +41 79 406 49 83

peter.felder@pewatron.com

Sales Other Countries / Product Management

Pressure Sensors

Philipp Kistler
Phone +41 44 877 35 03
philipp.kistler@pewatron.com

Accelerometers / Level Flow sensor elements

Thorsten Ravagni
Phone +49 60 479 53 627
thorsten.ravagni@pewatron.com

Drive technology CH Postcode 5000 – 9999 / DE

Roman Homa
Mobile +41 76 444 00 86
roman.homa@pewatron.com

Gas sensors / Gas sensor modules Load cells

Dr. Thomas Clausen
Phone +41 44 877 35 13
thomas.clausen@pewatron.com

Power supplies

Sebastiano Leggio
Phone +41 44 877 35 06
sebastiano.leggio@pewatron.com

Drive technology CH Postcode 1000 – 4999 / AT / IT / FR

Christian Mohrenstecher
Mobile +41 76 444 57 93
christian.mohrenstecher@pewatron.com

Flow / Level / Medical products

Dr. Adriano Pittarelli
Phone +49 8245 774 95 44
adriano.pittarelli@pewatron.com

Linear position sensors Angle sensors

Eric Letsch
Phone +41 44 877 35 14
eric.letsch@pewatron.com

Current sensors Power solutions

Osman Coban
Phone +49 71 635 363 898
osman.coban@pewatron.com